## **Industrial Mobile Computer**

# RT40C

- Qualcomm Octa-core 1.8GHz high-efficiency processor and cutting-edge Android Q operating system, gives you unparalleled performance.
- 29 keys island-style keyboard + 4" giant touch screen, intuitive operation reaction, accurate even with glove hands.
- Built-in industrial-leading scan engine, captures 1D/2D barcodes on screen and paper even if they are contaminated, wrinkled or distorted. 15m long-range version is optional.
- Hot-swap battery design, exchanges exhausted battery without reboot. Increase your efficiency.



IP68 Waterproof 1.8m Drop Resistance



Seamless WiFi Roaming 4G Communication



13M Pixel AF Camera



4"Touch Screen Corning Gorilla glass



**Enterprise Enabler** 





## **RT40C Industrial Mobile Computer**

## Specifications







4GB RAM/64GB ROM, 3GB RAM/32GB ROM, microSD card, Max.128GB extension.



#### Screen

4 inch 480\*800 pixel Corning Gorilla glass



#### **Dimensions**

199 x 58(handle) x29(thinnest) mm (78.34 x 22.83 x 11.41 in)



Optional pistol grip version, with scan trigger key



#### **Main battery**

3.85V 5.200mAh, Support battery swap, exchange battery without boot-up, Charging time: Less than 3 hours.



#### Audio

Earpiece, speaker, microphone Support PTT (Push-to-Talk), speaker loudness over 100dB at 10cm.



#### Scanner

Standard range scanner and extended range scanner are optional Support all industry-leading 1D/2D barcode on paper or screen



Rear camera: 13M pixel with flashlight. (Not supported for pistol grip version).



29 keys isolation keyboard



#### Bluetooth

Bluetooth 5.0 BR/EDR BLE



## Wi-Fi

802.11 a/b/g/n/ac/d/e/ h/i/k/r/v/w 2.4GHz/5GHz



#### Sensor

Light sensor, proximity sensor, e- compress (optional)



#### Slot

Nano SIM\*1. PSAM/SIM\*1 (self-adaption).



#### **WWAN**

4G, 3G, 2G



GPS, Beidou, GLONASS, Galileo.



#### Sealing

1.8m (5.9 ft.) flat concrete.



## இ≡ Environment

Working temperature:-20  $\sim$  +50°C Storage temperature:-40  $\sim$  +70°C  $(-40^{\circ}F^{\sim} + 158^{\circ}F)$ , Humidity:5%RH $\sim$ 95%RH (non-condensing), ESD: ±15kV air, ±8kV direct.